

TECHNICAL DATA SHEET

EVA Protection Tape

VPP-50

Product Description

VDS-90 is a EVA protection tape coated with EVA adhesive, which used for glass, plastics, LCD protection.

Product Features

- High transparency, bright surface luminance.
- Good and steady adhesion.
- No residue when remove the film.

Main applications

- Protection for glass, plastics, LCD, sandwich panel of aluminum

Product composition

Substrate:	PE film
Adhesive:	EVA

Product Properties

Index (test standard)	Unit	Spec.
Total thickness	(μm)	50
Tensile strength GB/T7753-1987	(N/10mm)	≥ 8
Peel Adhesion GB/T2792-1998	(gf/25mm)	1 \pm 0.5
Elongation GB/T7753-1987	(%)	≥ 150

Note: The data include is tested in lab ($23 \pm 5^\circ\text{C}$, $55 \pm 10\%$ R.H.) it is the average value, the single one maybe a little bit different.

Specification:

Colour: clear

Finish roll size: as per customer's requirement

For details please contact with our sales.

Usage guidelines:

- Surfaces to which tape is applied should be clean, dry and free of grease, oil, moisture, dirt and other contaminants.
- It may affect the property when the surface is not even or badly damaged. To make the surface even as much as
- Sufficient pressure should be applied during application. It will affect the properties and appearance if the pressure is not enough.
- Peel build up needs time and it should not stretch or peel during in-use within several hours' application.
- Using the release paper to separation between two rolls before packaging. Do not use PE shrink film packaging.
- This tape is applied to the temperature from 10°C to 38°C , we suggest do not use it below 0°C .

★ Individual rolls may vary slightly from the above values. The user should try use and determine whether the product is suitable for his particular applications. If the user not try use the product and result in loss, the user should take responsibility for their own. If it is proved that our products have defects, we can make the sales return or get the product repair for our customers.

Storage condition:

- Shelf life 12 months from date of production. Tape should be stored in a cool (temperature between $10^\circ\text{C} \sim 35^\circ\text{C}$), dry (humidity below 60%) environment.
- Well ventilated area away from sunlight, air conditioner and other heat sources.
- Tape should be stored in original dry carton, off from the floor. Tape jumbos should be placed vertically in its original well package and avoid to be pressed against glue surface.

Contact:

Shanghai Vaneter Speacial Adhesive Tapes Co., Ltd.

Address: No. 69, Rongyang Road, Songjiang District

TEL: 021-37837338/37837336

E-mail: vaneter@126.com