

## TECHNICAL DATA SHEET

Super clear bopp tape

### VSC-50

#### Product Description

VSC-50 is a crystal clear BOPP tape. It can be applied to the carton sealing, light duty packaging.

#### Product Features

- Good performance in adhesion
- Convenient use, low cost
- Easy adherence to slightly irregular surfaces, due to good tack and strong substrate

#### Main applications

- Used in carton sealing
- Used in light duty packaging

#### Product composition

Substrate:	BOPP Film
Adhesive:	Acrylic

#### Product Properties

Index (test standard)	Unit	Spec.
Total thickness	( $\mu\text{m}$ )	50
Peel Adhesion ASTM D-1000	(kg/cm)	0.24
Elongation PSTC-131	(%)	140
Tensile strength PSTC-131	(hr)	$\geq 2$

Note: The data include is tested in lab ( $23 \pm 5^\circ\text{C}$ ,  $55 \pm 10\%$  R.H.) it is the average value, the single one maybe a little bit different.

#### Specification:

Colour: Transparent

Finish roll size: as per customer's requirement

For details please contact with our sales.

#### Usage guidelines:

- Surfaces to which tape is applied should be clean, dry and free of grease, oil, moisture, dirt and other contaminants.
- It may affect the property when the surface is not even or badly damaged. To make the surface even as much as possible.
- Sufficient pressure should be applied during application. It will affect the properties and appearance if the pressure is not enough.
- Peel build up needs time and it should not stretch or peel during in-use within several hours' application.
- Using the release paper to separation between two rolls before packaging. Do not use PE shrink film packaging.
- This tape is applied to the temperature from  $10^\circ\text{C}$  to  $38^\circ\text{C}$ , we suggest do not use it below  $0^\circ\text{C}$ .

★ Individual rolls may vary slightly from the above values. The user should try use and determine whether the product is suitable for his particular applications. If the user not try use the product and result in loss, the user should take responsibility for their own. If it is proved that our products have defects, we can make the sales return or get the product repair for our customers.

#### Storage condition:

- Shelf life 12 months from date of production. Tape should be stored in a cool (temperature between  $10^\circ\text{C}$ ~ $35^\circ\text{C}$ ), dry (humidity below 60%) environment.
- Well ventilated area away from sunlight, air conditioner and other heat sources.
- Tape should be stored in original dry carton, off from the floor. Tape jumbos should be placed vertically in its original well package and avoid to be pressed against glue surface.

#### Contact:

Shanghai Vaneter Special Adhesive Tapes Co., Ltd.

Address: No. 69, Rongyang Road, Songjiang District

TEL: 021-37837338/37837336

E-mail: vaneter@126.com